



Quick automatic calibration of fuel tank with high accuracy

Tank calibration table is saved directly to sensor's memory (only for DUT-E, DUT-E GSM, DUT-E 2Bio).

Speeds up tank calibration by 2-3 times.

"Human reliability" does not affect accuracy of calibration.

Calibration control from smartphone over Bluetooth.

Mobile app for calibration station can be downloaded from Google App store.

Two operation modes – automatic and semi-automatic

Autoshutdown in event of pressure/temperature excess.



Example: calibration of 500-liter fuel tank

ATS-1, automatic mode: ⌚ 20 minutes

Technician, calibration at gas station: ⌚⌚ 40 minutes

Technician, calibration with canister: ⌚⌚⌚ 60 minutes



Delivery set includes filling and suction hoses with camlock fittings.

Specifications

Tank calibration speed	1500 l/h
Relative inaccuracy of calibration	less than 0,5%
Dimensions (LxWxH)	700x335x335 mm
Weight of ATS-1 set*	23 ... 27 kg

* delivery set includes suction hose, filling hose with fuel nozzle, fuel sensor cable extender.



Phone +375 17 240 39 73
 Viber/WhatsApp +375 44 792 67 58
 e-mail: sales@technoton.by
 www.jv-technoton.com

